

**This Page Is Inserted by IFW Operations  
and is not a part of the Official Record**

## **BEST AVAILABLE IMAGES**

**Defective images within this document are accurate representations of the original documents submitted by the applicant.**

**Defects in the images may include (but are not limited to):**

- **BLACK BORDERS**
- **TEXT CUT OFF AT TOP, BOTTOM OR SIDES**
- **FADED TEXT**
- **ILLEGIBLE TEXT**
- **SKEWED/SLANTED IMAGES**
- **COLORED PHOTOS**
- **BLACK OR VERY BLACK AND WHITE DARK PHOTOS**
- **GRAY SCALE DOCUMENTS**

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning documents *will not* correct images,  
please do not report the images to the  
Image Problem Mailbox.**

*Please amend claims 1 and 7*

**၀၀၀၁၂၃၄၅၆၇၈၉၀၁၂၃၄၅၆၇၈၉၀**

000000000000000000'00

**bjb**

၎င်းတို့သည် အောက်ဖော်ပြပါအတိုင်း ဖြစ်ပေါ်ခဲ့သည်။

တတိယအဆင့်အထိရှိသော အထကအထိရှိသည့် ကျား၊ မိန်းမတို့၏ ပညာရေးအဆင့်ကို ဖော်ပြသည့် အချက်အလက်များကို အောက်ဖော်ပြပါဇယားတွင် ဖော်ပြထားပါသည်။

second layer being positioned above the plurality of turns of a first layer, wherein

the turns (N(L1)) in said first layer (L1) are arranged parallel to one another, and the turns (N(L2)) in the second layer (L2) are inclined, at a predetermined point at a predetermined inclination angle (a), with respect to the turns ((N(L1)) in the first layer (L1), and wherein the plurality of turns in the second layer are arranged parallel alongside one another wherein the inclination angle (a) is such that each turn (N(L2)) in the second layer (L2) is inclined by at least one pitch width.

2. (Cancelled)

3. (Original) The coil arrangement according to claim 1, wherein an individual turn (N(L1), N(L2)) in one of the layers (L1, L2) is inclined by a total pitch width (G), which is formed by a total number of pitches in an adjacent layer (L1, L2).

4. (Original) The coil arrangement according to claim 1, wherein a coil start (S(A)) and coil (S(E)) are passed out jointly at one end winding, with the turns (N(L2)) in the second layer (L2) at an opposite end winding being inclined at the inclination angle (a).

5. (Original) The coil arrangement according to claim 4, wherein the end windings are domed outwards.

6. (Original) The coil arrangement according to claim 1, wherein the plurality of turns (N(L1), N(L2)), in one of said layers (L1, L2) are arranged parallel alongside one another, partially superimposed.

7. (Currently Amended) A method for producing a coil arrangement for an electrical machine, comprising the steps of:

winding an electrical conductor on a coil former with a first plurality of turns to form a second layer on and above said layer, wherein the step of forming said second layer includes the step of bending the electrical conductor through a predetermined bending angle at a predetermined point before ~~each turn of~~ said second plurality of turns is wound on said coil former.

8. (Original) The method according to claim 7, wherein the turns in the first layer are wound parallel alongside one another, with the turns in the second layer being inclined through the bending angle with respect to the first layer and being arranged parallel alongside one another.

9. (Original) The method according to Claim 7, wherein the bending angle is such that each turn in the second layer is inclined by at least one pitch width.

10. (Original) The method according to Claim 7, wherein one turn in one of the layers is inclined by the total pitch width, which is formed by the total number of pitches in an adjacent layer.

11. (Original) The method according to Claim 7, wherein a coil start and coil end are passed out jointly at one end, with the turns in the second layer at the opposite end winding being inclined at the bending angle before being wound on to the coil former.

12. (Original) The method according to Claim 7, wherein the turns in a single layer are wound parallel alongside one another, partially superimposed.

13. (Withdrawn) An apparatus for winding an electrical conductor with a number of turns arranged above each other in a number of layers, comprising:

a guide body;

a coil former wherein the guide body is provided for winding the electrical conductor on to said coil former;

and wherein said guide body bends the electrical conductor through a bending angle at a predetermined point before a coil turn is wound on to said coil former.

14. (Withdrawn) The apparatus according to Claim 13, wherein said guide body is movable.

15. (Withdrawn) The apparatus according to Claim 13, wherein said guide body includes a motor for moving two bending pins.